

- Built-in microSD slot
- Built-in microphone
- Metal casing
- Support for PoE
- IR illumination up to 40 m
- Configuration via web interface
- ONVIF



**SV-BA314-E** wired IP camera with a dome design provides a horizontal viewing angle of  $100^{\circ}$  and is equipped with a 4 MP CMOS matrix for clear video with a resolution of up to  $2560 \times 1440$ . The device has a night shooting mode (IR illumination), motion detection system and the function of saving the video archive to a memory card or network storage<sup>1</sup>. The camera is equipped with a RJ-45 connector with support for basic network protocols.

#### Technical features

echnical features		
Interfaces		
Ethernet	$1 \times 10/100$ BASE-T (RJ-45), support for PoE	
Memory card	1 × MicroSD/SDHC/SDXC up to 256 GB	
	Operating system	
Linux SDK		
	Sensor	
Туре	1/3" progressive scan CMOS	
Effective pixels	4M	
	Lens and illumination	
Focal distance	2.8 mm	
Aperture	F/2.0	
Field of view (horizontal)	100°	
Field of view (diagonal)	116°	
Angle adjustment (tilt)	from 0° to 105°	
Angle adjustment (rotate)	from 0° to 360°	
IR illumination	yes	
IR range	up to 40 m	
	Image	
Maximum resolution	2560 × 1440	
Maximum frame rate	25 fps	
Bit rate	up to 10 Mbps	
Video compression	H.264, H.265	
Image quality improvement	DNR 2D/3D, DWDR, BLC, AE, AWB, HLC, ANTI-FLICKER, DEFOG, ROI <sup>1</sup>	
Signal-to-noise ratio	no less than 50 dB	
Minimum illumination	color: 0.01 lx, bw: 0 lx with IR	

<sup>1</sup> Under development.

1 www.eltex-co.com



# **Technical features (continued)**

	Audio	
Built-in microphone	yes	
Audio compression	PCM, AAC, MP2, ADPCM <sup>1</sup> , G.711U (PCMU) <sup>1</sup> , G.711A (PCMA) <sup>1</sup> , G.726 <sup>1</sup>	
Voice pickup distance	up to 5 m	
Physical specifications		
Power supply	12 V DC, PoE 802.3af	
RAM	128 MB	
ROM	32 MB	
Casing	metal, plastic	
Form factor	dome camera	
Mount options	indoor and outdoor	
Dimensions (Height × Diameter)	90 × 110 mm	
Weight	0.39 kg	
Operating temperature	from -40 to +60 °C	
Operating humidity	no more than 90 % (non-condensing)	
Ingress Protection	IP67	

# Analytics and protocols<sup>1</sup>

- Face recognition
- Motion detection
- Human detection
- Line crossing detection
- Perimeter intrusion detection
- ONVIF (Profile S, T)

#### **Features and capabilities**

- Night vision
- Storage: memory card, network storage<sup>1</sup>
- Management via web interface
- Non-volatile time (up to 24 hours)

# **Ordering information**

Name	Description
SV-BA314-E	SV-BA314-E wired IP camera. Mounting kit.

<sup>&</sup>lt;sup>1</sup> Under development.

Contact us About ELTEX







**ELTEX** Enterprise is a leading Russian developer and manufacturer of communication equipment with 30 years of history. Complete solutions and their seamless integrability into the Customer's infrastructure are the priority growth areas of the company.